DATA SHEET NPD30B

Wall mount AC/DC USB Type-C Power adapter 36W



SUMMARY

This specification defines the performance and characteristics of a wall mount AC/DC USB TYPE-C adapter designed by NetBit for the latest CPE product applications for high volume deployment.

USER BENEFITS

- Compact size – designed to maximise shipping efficiency and reduce total transportation costs
- High efficiency – optimized to exceed latest energy efficiency standards for lower total power consumption
- CPE ready – built to meet and exceed the operating requirements for all CPE applications and installations
- Reliable – engineered to high standards to give a long and reliable service for operators and end users
- MTBF >50 years at 25°C and >25 years at 45°C ambient, according MIL HBDK 217 standard
- MTBF>500,000 Hours at 40°C ambient, according Bellcore SR 332 standard
- Continuous operational lifetime :>7 years at 25°C and >3 years at 45°C ambient
- Compliant with the latest PD3.2 standard and USB-IF specifications
- Supports custom VDM message definition
- Compliant with (EU) 2025/2052 common-charger requirements

OPTIMISED CONNECTED USER EXPERIENCE

- Lower leakage current
- Enhanced safety - open neutral - PWM IC with bulk-OVP function
- Optimisation for QLN and PLT.

ECO BENEFITS

- Heatsink-free design: reduces cost
- Smaller enclosure: less plastic, more per container.
- Post-consumer recycled case options: reduced virgin plastic
- SUP free packaging options

APPLICATIONS

- Set-top boxes and PVRs; cable, satellite, hybrid/IP
- Gateways: DSL,DOCSIS 3.0 and 3.1, G-PON

© 2026 NetBit Electronics Ltd. This document is confidential and proprietary to NetBit Electonics Ltd.
All Rights Reserved. No part of this document may be copied of reproduced, in whole or in part, in any material form (including photocopying and/or storage in any medium by electronic means and whether of not transiently or incidentally to some other use of this document) without the written permission of NetBit Electonics Ltd.

NetBit®
POWERING YOUR IDEAS

AC INPUT

Rated input voltage: 200-240VAC
Operating range: 180 to 264Vac

Rated input frequency: 50/60Hz
Wall mount AC plug: EU/UK
No load power consumption: ≤0.075W

DC OUTPUT

Output: 5V3A/9V3A/15V2.4A

Load/line regulation: +/- 5%
OVP: 19.5V Max. or custom

OCP: 160% Max. or custom

Hold-up time: ≥10ms

Turn on delay: <3000ms

Overshoot / undershoot ≤5%

Audible noise: <25dBA at 300mm
Ripple: <150mVp-p

OPERATIONAL

Operating temperature range: 0 – 45°C
Altitude: 0 – 5,000m operational, 0 – 12,000m non-op
Humidity: 0 – 95% non-condensing

MECHANICALS

Color: black or custom.
Plug USB Type-C
DC CC cable options:20AWG 1.8m or custom
LED:Green or custom

REGULATORY COMPLIANCE

EMI: CE + RE: EN 55032 Class B: EN 55035
ESD: EN 61000-4-2 15kV Air / 8kV Contact
Surge: designed with enhanced and robust surge immunity; 6kV ,K.21 standard

SHIPPING & PACKAGING

Carton quantity: 72pcs

Pallet quantity: 1728pcs

Full container load 20'GP:38016PCS

CERTIFICATIONS

Safety: IEC 62368-1, UL, CE
Environmental: RoHS/REACH compliant
Efficiency: CoC-V5.2 and (EU)2025/2052

CASE DIMENSIONS

Wall mount
Width: 34mm
Height: 40mm
Length: 79mm



RoHS DIRECTIVES

RoHS 2.0
Case produced using PC PAHS 6P NP REACH ROHS NOP

For more information on NetBit products, please visit our website - www.netbit.com

© 2026 NetBit Electronics Ltd. This document is confidential and proprietary to NetBit Electonics Ltd.
All Rights Reserved. No part of this document may be copied of reproduced, in whole or in part, in any material form (including photocopying and/or storage in any medium by electronic means and whether of not transiently or incidentally to some other use of this document) without the written permission of NetBit Electonics Ltd.

NetBit®
POWERING YOUR IDEAS